

Type aM

Calibre (A)	Tension (V)	Pouvoir de coupure (kA)	Réf sans percuteur	Réf avec percuteur	Pkg Pce
10 x 38 mm - HPC					
2	500	120	0.601.02	-	10
4	500	120	0.601.04	-	10
6	500	120	0.601.06	-	10
10	500	120	0.601.10	-	10
16	500	120	0.601.16	-	10
20	500	120	0.601.20	-	10
25	400	120	0.601.25	-	10



Type gG Industriel

Calibre (A)	Tension (V)	Pouvoir de coupure (kA)	Réf sans voyant	Réf avec voyant	Pkg Pce
10 x 38 mm - HPC					
1	500	120	0.610.01	-	10
2	500	120	0.610.02	0.611.02	10
4	500	120	0.610.04	-	10
6	500	120	0.610.06	0.611.06	10
10	500	120	0.610.10	0.611.10	10
16	500	120	0.610.16	-	10
20	500	120	0.610.20	-	10
14 x 51 mm - HPC					
10	500	120	-	0.613.10	10
32	500	120	0.612.32	-	10
22 x 58 mm - HPC					
20	660	120	0.614.20	-	10
32	660	120	0.614.32	-	10



Type gG Domestique

Calibre (A)	Tension (V)	Pouvoir de coupure (kA)	Réf sans voyant	Réf avec voyant	Pkg Pce
8.5 x 23 mm					
2	230	6	0.624.02	-	10
4	230	6	0.624.04	-	10
10	230	6	0.624.10	0.644.10	100
10.3 x 25.8 mm					
10	230	6	0.625.10	-	10
16	230	6	0.625.16	0.645.16	100
8.5 x 31.5 mm					
6	400	20	0.631.06	-	10
10	400	20	0.631.10	-	10
12	400	20	-	-	10
16	400	20	-	0.661.16	100
20	400	20	0.631.20	0.661.20	100
10.3 x 38 mm					
32	400	20	0.638.32	0.668.32	10

